

Removal of fluoride from photovoltaic wastewater by electrocoagulation and products characteristics

N. Drouiche^{a,b*}, H. Lounici^b, M. Drouiche^b, N. Mameri^b, N. Ghaffour^c

^a*Silicon Technology Development Unit (UDTS), 2, Bd Frantz Fanon BP399, Algiers, 16000, Algeria
Tel./Fax +213 21433511; email: najibdrouiche@yahoo.fr*

^b*Laboratory of Environmental Biotechnologies, Ecole nationale Polytechnique d'Alger, 10, Av. Hassene Badi El-Harrach, Algiers, Algeria*

^c*Middle East Desalination Research Center, P.O. Box21, P.C.133, Muscat, Sultanate of Oman*

Received 13 July 2008; Accepted ion revised form 9 June 2009

ABSTRACT

Efficient treatment of fluoride-containing wastewater efficiently has been important for environmental engineers in Algeria. An appropriate concentration of fluoride in drinking water is required to prevent dental cavities, but long-term ingestion of water that contains more than a suitable level of fluoride causes bone disease and mottling of the teeth. The CMP wastewater from a UDTS. was characterized by high suspended solids (SS) content, chlorates, hydroxylamine, high turbidity (NTU), chemical oxygen demand (COD) concentration up to 7.00 mg l⁻¹ and fluoride concentration up to 1000 mg l⁻¹. Currently, the cheapest way to remove fluoride from semiconductor wastewater is to produce calcium fluoride (CaF₂) by adding lime or another calcium salt. The aim of this paper is to propose an efficient and low cost treatment of chemical mechanical polishing wastewater process based on electrocoagulation with iron bipolar electrodes. The performance of a pilot scale electrochemical reactor equipped with iron bipolar electrodes and an anode active area surface of about 170 cm² was studied. In addition, sludge settling after electrocoagulation was characterized.

Keywords: Fluoride removal; Physicochemical interaction; Sludge structure; Iron bipolar electrode

* Corresponding author.