

Corrigendum

Modelling and optimizing Orange G removal by heat-activated persulfate using two-step statistical strategies: Plackett–Burman and Box–Behnken designs*

Naima Habache^{a,b}, Ouahiba Bechiri^{a**}, Ilhem Djaghout^{b,c}, Meriem Djenouhet^d

^aLaboratory of the Environmental Engineering, Department of the Process Engineering, Faculty of Engineering, University

of Badji Mokhtar, Annaba, Algeria, emails: bechirio@yahoo.fr (O. Bechiri), naimahabache28@gmail.com (N. Habache)

^bDepartment of the Process Engineering, Faculty of Science and Technology, University Mohamed-Cherif Messaadia, Souk Ahras, Algeria, email: i.djaghout@univ_soukaras.dz (I. Djaghout)

^cLaboratory of Industrial Analysis and Materials Engineering, University 8 May 1945 of Guelma, Algeria

^dLaboratory LOMOP, Department of the Process Engineering, Faculty of Engineering, University of Badji Mokhtar, Annaba, Algeria, email: djanomari@yahoo.fr

In the original version of the article "Modelling and optimizing Orange G removal by heat-activated persulfate using two-step statistical strategies: Plackett–Burman and Box–Behnken designs" published in vol. 244, December 2021, pp. 291–301, the name of Meriem Djenouhet was misspelled. The corrected version has subsequently been published.

**Corresponding author

^{*}doi number of the original article is 10.5004/dwt.2021.27904

^{1944-3994 / 1944-3986 © 2022} Desalination Publications. All rights reserved.